

What is claimed is:

1           1(currently amended).     An arrangement for attaching hygienic articles  
2     such that their height will be adjustable, comprising:  
3           a wall-mounting rod that has a continuous, guiding profile for guiding a  
4     slide, **the guiding profile having a slot open to a front side of the wall-**  
5     **mounting rod and open to both end faces** ~~extending over a full length of the~~  
6     wall-mounting rod ~~between ends,~~ **and,**  
7           at least one bracket for fastening the wall-mounting rod to a surface,  
8     wherein the arrangement leaves clear ~~that part of~~ the guiding profile used for  
9     guiding the slide.

1           2(currently amended).     An arrangement according to claim 1, where  
2     the bracket is attachable to the wall-mounting rod in the vicinities of the **end**  
3     **faces** ~~ends~~.

1           3(previously presented).   An arrangement according to claim 1, wherein  
2     the bracket is attachable to the wall-mounting rod by one of inserting the  
3     bracket into the wall-mounting rod, and latching the bracket onto the wall-  
4     mounting rod.

1           4(currently amended).     An arrangement according to claim 1, ~~having~~  
2     ~~plural,~~ **wherein the at least one bracket includes a plurality of** at least  
3     partially identically shaped said brackets.

1           5(previously presented).   An arrangement according to claim 1, where  
2     the at least one bracket is configured for attachment to two sections of a wall-  
3     mounting rod that are to be coaxially arranged.

1           6(currently amended).     An arrangement according to claim ~~4~~ **4**,  
2     **where the brackets are configured for attachment to two sections of a**  
3     **wall-mounting rod that are to be coaxially arranged,** where the **brackets**  
4     **have** ~~at least one bracket has~~ two attachment sections, **said attachment**  
5     **sections of the brackets being engageable with ends of the two sections**  
6     **of the wall-mounting rod at a joint** ~~one each at least near to each of the ends,~~  
7     one of **the attachment sections of the brackets being** ~~which is~~ configured for  
8     attaching a terminating component for terminating **one of the two sections of**  
9     the wall-mounting rod **at an other end of said one of the two sections of the**  
10    **wall mounting rod.**

1           7(previously presented).     An arrangement according to claim 6, where  
2     the attachment section for attaching the terminating component has a device for  
3     one of a form-fit and an interference-fit attachment of the terminating  
4     component.

1           8(currently amended).     An arrangement according to claim 6, where  
2     both attachment sections **of the bracket** have means for guiding the sections of  
3     the wall-mounting rod.

1           9(currently amended).     An arrangement according to claim 6, where  
2     the two attachment sections **of the bracket** are separated by a land.

1           10(currently amended).     An arrangement according to claim 1, where  
2     the wall-mounting rod has a groove forming **the** ~~a~~ guiding profile **and opening**  
3     **at the slot.**

11(currently amended). **An arrangement for attaching hygienic articles such that their height will be adjustable, comprising:** ~~An arrangement according to claim 10, where~~  
**a wall-mounting rod that has a continuous, guiding profile for guiding a slide, extending over a full length of the wall-mounting rod between ends,**  
**at least one bracket for fastening the wall-mounting rod to a surface, wherein the arrangement leaves clear that part of the guiding profile used for guiding the slide,**  
**wherein the guiding profile includes a groove, and further comprising** a lower terminating component **including** ~~has~~ an extension of the groove.

12(Previously presented). An arrangement according to claim 1, where the wall-mounting rod forms a length of stock with a hollow profile and the bracket engages an interior of the hollow profile.

13(Previously presented). An arrangement according to claim 1, where accessory items are attachable to the bracket.

14(Previously presented). An arrangement according to claim 6, wherein the terminating component comprises a terminating collar.

15(Previously presented). An arrangement according to claim 9, wherein the land forms a joint.

16(Previously presented). An arrangement according to claim 10, wherein the groove is on a front surface of the wall-mounting rod.

1           17(currently amended).           **An arrangement for attaching**  
2           **hygienic articles such that their height will be adjustable, comprising:**  
3           ~~An arrangement according to claim 13,~~  
4           **a wall-mounting rod that has a continuous, guiding profile for**  
5           **guiding a slide, extending over a full length of the wall-mounting rod**  
6           **between ends,**  
7           **at least one bracket for fastening the wall-mounting rod to a**  
8           **surface, wherein the arrangement leaves clear that part of the guiding**  
9           **profile used for guiding the slide, and,**  
10          wherein ~~the~~ accessory items are attachable to the bracket at a land  
11          separating two attachment sections.

1           18(previously presented). An arrangement according to claim 17,  
2           wherein the land is broadened for attachment of the accessory items.